

- Pure sine wave solar inverter
- Output power factor 1
- Selectable high-power charging current
- Wide DC input range
- Selectable input voltage range for home appliances and personal computers
- Configurable solar input priority setting via LCD setting
- Compatible with mains voltage or generator power
- Auto restart while AC is recovering
- Smart battery charger design for optimized battery performance
- Overload and short circuit protection



Model	FCS VP 1-12	FCS VM 1-12	FCS VM 2-24	FCS VM 2-24	FCS VP 3-24	FCS VM 3-24	FCS VM 3-24 +	FCS VP 5-48	FCS VM 5-48	
Rated Power	1000VA/1000W		2000VA/2000W		3000VA / 3000W		5000VA / 5000W			
INPUT										
Voltage	230 VAC									
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)									
Frequency Range	50 Hz/60 Hz (Auto sensing)									
OUTPUT										
AC Voltage Regulation (Batt.Mode)	230VAC ± 5%									
Surge Power	2000VA	4000VA		6000VA			10000VA			
Efficiency (Peak)	90% ~ 93%									
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)									
Waveform	Pure sine wave									
BATTERY										
Battery Voltage	12 VDC	24 VDC						48 VDC		
Floating Charge Voltage	13.5 VDC	27 VDC						54 VDC		
Overcharge Protection	16 VDC	33 VDC						63 VDC		
SOLAR CHARGER & AC CHARGER										
Solar Charger type	PWM	MPPT	PWM	MPPT	PWM	MPPT		PWM	MPPT	
Maximum PV Array Open Circuit Voltage	55 VDC	102 VDC	80 VDC	102 VDC	80 VDC	102 VDC	145 VDC	105 VDC	145 VDC	
Maximum PV Array Power	600 W	500 W	1200 W	1000 W	1200 W	1000 W	1500 W	2400 W	3000 W	
MPP Range @ Operating Voltage	N/A	17 ~ 80 VDC	N/A	30 ~ 80 VDC	N/A	30-80 VDC	30~115 VDC	N/A	60 ~ 115 VDC	
Maximum Solar Charge Current	50 A	40 A	50 A	40 A	50 A	40 A	60 A	50 A	60 A	
Maximum AC Charge Current	20 A	20 A	20 A	25 A	25 A	25 A	60 A	60 A	60 A	
Maximum Charge Current	50 A	60 A	50 A	60 A	70 A	60 A	120 A	110 A	120 A	
PHYSICAL										
Dimension, D x W x H (mm)	88 x 225 x 320				100 x 285 x 334		100 x 300 x 440	100 x 300 x 440		
Net Weight (kgs)	4.4				6.5		9.5	9.7		
Communication Interface	USB/RS232									
ENVIRONMENT										
Humidity	5% to 95% Relative Humidity (Non-condensing)									
Operating Temperature	-10 to 50 °C									
Storage Temperature	-15 to 60 °C									